



A INTERPRETABLE QUANTUM-INSPIRED DEEP REINFORCEMENT LEARNING APPROACHES FOR LARGE-SCALE DATA ANALYTICS

G.S.Geethamani¹

¹Research Scholar, Department of Computer Science,
Sri Ramakrishna College of Arts & Science for Women, Coimbatore, India.

Email: gsgeethamani@gmail.com

D.Anitha²

²Associate Professor, Department of Computer Science,
Sri Ramakrishna College of Arts & Science for Women, Coimbatore, India.

Email: anithacs@srcw.ac.in

Orchid id: <https://orcid.org/0009-0009-2846-7378>

Abstract

The rapid expansion of large-scale data analytics (LSDA) has presented significant issues concerning computing efficiency, scalability, adaptive learning, and model interpretability. In recent years, quantum-inspired deep reinforcement learning (QIDRL) has emerged as a promising research paradigm that integrates quantum-inspired optimization (QIO) concepts with deep reinforcement learning (DRL) approaches to enhance intelligent decision-making and complicated data processing. The need for transparent and reliable artificial intelligence (AI) systems has heightened the significance of interpretable learning frameworks that can elucidate model behavior and prediction results. This work offers a thorough examination of interpretable QIDRL methods for extensive data analysis. The review methodically examines current advancements in QIO models, interpretable RL architectures, policy explanation mechanisms, and scalable deep learning (DL) frameworks used for high-dimensional and dynamic datasets. The report examines the use of these methodologies across many sectors, including healthcare analytics, cybersecurity, smart transportation, industrial automation, financial forecasting, and intelligent Internet of Things (IoT) ecosystems. The study examines the benefits of QIDRL techniques in improving convergence speed, adaptive decision-making, feature optimization, and interpretability inside extensive analytical systems. Furthermore, significant research obstacles like computational complexity, training instability, scalability limitations, insufficient benchmark datasets, and the absence of defined criteria for interpretability assessment are thoroughly examined. The study emphasizes new research trends and prospects for creating robust, efficient, and transparent QIDRL frameworks for advanced intelligent DA applications.

Keywords: Large-Scale Data Analytics, Quantum-Inspired Deep Reinforcement Learning, Quantum-Inspired Optimization, Deep Reinforcement Learning, Artificial Intelligence, Deep Learning, Cybersecurity, Internet of Things

1. Introduction

The rapid development of LSDA of modern intelligent systems has greatly increased the need for advanced computational models that are capable of efficiently handling high-dimensional,



heterogeneous, and dynamic data. DL methods have been very successful in the areas of healthcare, cybersecurity, finance, smart transportation, industrial automation, and the IoT ecosystem. Deep neural networks commonly face problems with computational complexity, scalability, energy consumption, and interpretability. To tackle these challenges, researchers have paid increasing attention to the integration of quantum-inspired computing principles with DRL frameworks to enhance learning efficiency, adaptive decision-making, and optimization capabilities in large-scale analytical environments [1]. The QIDRL combines the benefits of quantum computational principles, such as superposition, probabilistic representation, and quantum state optimization, with RL schemes to enhance intelligent data processing and autonomous learning efficiency.

Interpretable AI has become a crucial subject of research, especially in recent years, with the increasing use of AI systems in sensitive and mission-critical environments [2]. DRL models have strong decision-making skills, but the black-box aspect makes it difficult to understand the prediction behavior, policy choice, and model reliability. This has led to much interest in interpretable QIDRL approaches, since they provide visible and elucidative learning processes while maintaining better computer efficiency [3]. Recently, it has been shown that the quantum-inspired RL models can have a significant improvement in the optimization accuracy, convergence speed, and adaptive learning ability in complex environments such as robotics navigation, renewable energy management, database optimization, and financial market prediction [4].

The integration of quantum-inspired neural networks (QINN) with interpretable learning frameworks has enabled researchers to construct scalable and trustworthy intelligent systems for big data analytics. Hybrid quantum neural networks, quantum attention mechanisms, explainable policy-learning frameworks, and QIO algorithms are some of the advanced methods that have shown impressive effectiveness for large datasets and nonlinear analytical problems [5]. Still, the other research difficulties are not addressed, e.g., training instability, computational cost, no specified interpretability measurements, hardware limitations, and insufficient testing strategies for large-scale real-world applications. In this work, we investigate the recent methods, applications, advantages, limitations, and future directions of the interpretable QIDRL

techniques for large-scale data analytics. We provide a comprehensive survey of QDRL in terms of building robust, scalable, and interpretable intelligent analytical systems.

1.1. Problem Statement

The fast development of large-scale data analytics in current intelligent systems has raised substantial issues in terms of data complexity, scalability, computing efficiency, adaptive learning, and model transparency. Conventional DL and RL algorithms are very effective in finding complex patterns in large-scale data; however, they suffer from many disadvantages, such as high computational load, slow convergence, high power consumption, and a lack of interpretability of the decision-making process. The absence of transparent explanations for model predictions and policy choices in crucial application areas such as healthcare, cybersecurity, industrial automation, smart transportation, and financial analytics has resulted in decreased user confidence, less dependability, and less practical adoption of intelligent systems. Although QIO methods have exhibited promising



capabilities recently in improving learning efficiency, feature optimization, and decision accuracy, the existing RL still face major challenges in interpretability, scalability, training instability, and lack of standardized evaluation frameworks. Moreover, most of the existing research mainly concentrates on performance improvement with little attention to transparent reasoning processes and explainable policy-learning procedures. There is a significant gap in large-scale data analytics due to the lack of unified architectures that can effectively integrate interpretability, QIO, and scalable RL. Consequently, there is a significant demand for a comprehensive review and analytical investigation of interpretable QIDRL approaches to identify existing methodologies, research challenges, practical limitations, and future opportunities for the development of robust, transparent, and computationally efficient intelligent analytics systems.

1.2. Motivation

The increasing dependence on big data analytics in intelligent systems necessitates the development of advanced learning models that are both computationally efficient and transparent, ensuring trustworthiness. DRL techniques have shown exceptional performance in prediction; nevertheless, their opaque nature limits interpretability, hence diminishing confidence in critical real-world applications such as healthcare, cybersecurity, finance, and intelligent industrial systems. Recently, QIO methods have shown significant potential for enhancing learning efficiency, accelerating convergence speed, and improving adaptive decision-making abilities. Notwithstanding these advantages, less research has been undertaken on integrating interpretability with QIDRL frameworks for scalable analytical contexts. This requires a comprehensive review of interpretable QIDRL methods, encompassing existing research deficiencies, assessment of current techniques, and prospective avenues for the advancement of dependable, explainable, and high-performance intelligent DA systems.

1.3. Contributions

- This study offers a comprehensive and methodical examination of interpretable QIDRL methodologies used in LSDA, including contemporary architectures, optimization techniques, and intelligent decision-making frameworks.
- The research examines several interpretability and transparency methodologies included in quantum-inspired RL models, including explainable policy learning, attention-based reasoning, feature significance assessment, and decision visualization strategies.
- This study analyzes the use of QIDRL models in many real-world sectors, including healthcare analytics, cybersecurity, financial forecasts, industrial automation, IoT systems, and smart transportation.
- This paper rigorously examines significant obstacles such as computational complexity, scalability concerns, training instability, insufficient benchmark datasets, hardware constraints, and the lack of defined criteria for interpretability assessment in current QIDRL systems.
- This paper emphasizes growing research possibilities and proposes future paths for creating robust, scalable, energy-efficient, and interpretable QIDRL frameworks for next-generation intelligent LSDA systems.



2. Related Works

Scalable, intelligent analytical systems for complicated data environments have been greatly enhanced by recent developments in quantum-inspired AI. A thorough analysis of quantum deep neural networks for prognostics and health management applications, emphasizing how quantum-enhanced learning models may improve fault detection, predictive maintenance, and healthcare monitoring systems. In addition to highlighting the significance of computational efficiency and adaptive learning capabilities, their work identified important obstacles, such as hardware constraints, model complexity, and a lack of interpretability in quantum neural architectures [6]. To examine different quantum machine learning techniques, uses, and new benefits in a variety of fields. In comparison to conventional ML techniques, the authors examined how quantum-inspired optimization and probabilistic learning processes may improve classification accuracy, feature representation, and decision-making performance [7].

The proposed QuantumNeuroXAI framework combines explainability approaches for brain signal analysis and neurological illness diagnosis with QDL in the context of explainable and interpretable learning systems. Their research showed how interpretable quantum-inspired models may enhance diagnostic reliability, feature significance analysis, and transparency in delicate healthcare applications [8]. Additionally, a thorough statistical study contrasting quantum and conventional neural networks in the medical field was carried out. According to their research, quantum-inspired learning models have the potential to increase optimization efficiency and predictive analytics, but they also present scalability and training stability issues in real-world deployment settings [9]. A multi-agent quantum-inspired DRL framework for real-time distributed generation control in renewable energy systems was also presented. In dynamic, large-scale contexts, the suggested method improved adaptive decision-making, optimized energy distribution, and increased system stability. Together, these results show interpretable quantum-inspired DRL techniques are becoming more important for creating effective, scalable, and transparent intelligent analytics systems for a variety of real-world applications [10].

Recent studies in deep reinforcement learning and quantum-inspired machine learning have shown significant advancements in creating clever and scalable analytical systems for challenging real-world applications. In order to enhance real-time analytics and high-speed computing performance, ultra-low latency quantum-inspired machine learning predictors are developed and implemented on FPGA platforms. In order to accelerate large-scale intelligent systems while lowering processing delays and computational overhead, their study demonstrated the significance of hardware-efficient quantum-inspired designs [11]. A more comprehensive overview of deep reinforcement learning techniques was provided, along with a discussion of the development of actor-critic models, policy-based learning, value-based optimization, and adaptive decision-making techniques that have had a major impact on contemporary intelligent analytics systems [12]. In a similar vein, it included a thorough analysis of deep learning principles, convolutional neural network topologies, difficulties, and potential future paths, highlighting the increasing significance of scalable neural models for intelligent automation and big data analytics [13].



Applying DL and quantum-inspired frameworks to biomedical analytics and healthcare has also been the subject of much research. To provide a reliable convolutional neural network-based framework that uses functional magnetic resonance imaging (fMRI) data to diagnose the severity of Alzheimer's disease. Their research showed how deep learning and sophisticated feature extraction techniques might enhance medical decision support systems and illness classification accuracy [14]. Additionally, to suggest quantum-inspired neural networks with stochastic dynamics for sarcasm detection and multimodal sentiment analysis. The work demonstrated that in natural language processing applications, quantum-inspired learning mechanisms may successfully improve contextual comprehension, emotional feature representation, and adaptive learning performance [15]. To demonstrate the efficacy of quantum-inspired intelligence in managing intricate biological datasets and computational genomics difficulties, researchers looked at quantum neural networks for protein post-translational modification, protein function prediction, and DNA sequence analysis [16].

Additionally, the integration of quantum learning methods with deep neural networks for object identification applications was explored. Their review demonstrated how quantum-inspired optimization techniques may enhance computer vision systems' computational scalability, detection accuracy, and feature extraction efficiency. Additionally, the use of machine learning techniques in molecular simulation was investigated, with a focus on the importance of intelligent learning frameworks for modeling intricate molecular interactions, physical systems, and scientific data analysis [17]. When taken as a whole, these studies show that quantum-inspired deep learning and reinforcement learning techniques are quickly developing into effective LSAD solutions that provide enhancements in computational efficiency, optimization, interpretability, and adaptive intelligence across a variety of interdisciplinary domains [18].

2.1. Research Gap:

Although existing studies [1]–[18] have demonstrated significant advancements in quantum-inspired ML, DRL, explainable AI, and LSAD, several critical research gaps remain unresolved. Most current approaches primarily focus on improving predictive accuracy, optimization efficiency, and computational performance, while limited attention has been given to integrating interpretability and transparency within QIDRL frameworks. Additionally, many existing models lack standardized explainability evaluation metrics, scalable architectures for ultra-large datasets, and stable training mechanisms for dynamic real-world environments. Several studies also concentrate on domain-specific applications such as healthcare, renewable energy, object detection, and sentiment analysis without providing generalized and unified interpretable frameworks applicable across multiple large-scale analytics domains. Furthermore, practical deployment challenges, including hardware constraints, high computational complexity, insufficient benchmark datasets, and limited real-time implementation support, continue to restrict the adoption of quantum-inspired intelligent systems. Therefore, there is a strong need for comprehensive research toward developing scalable, interpretable, computationally efficient, and robust quantum-inspired deep reinforcement learning models for next-generation large-scale data analytics applications.



3. Methodology

This paper's approach is to provide a comprehensive and systematic study of interpretable QIDRL methodologies for big data analytics. The collected works were thoroughly screened according to the main criteria of relevance, quality of research, field of application, and contribution to interpretable quantum-inspired intelligent systems. The selected articles were then classified into numerous study topics, including domain-specific large-scale analytics applications, explainable reinforcement learning frameworks, hybrid optimization models, interpretable policy-learning processes, and quantum-inspired neural architectures. In addition, a comparative research was performed to analyze the examined approaches, taking into account crucial performance criteria such as scalability, computational efficiency, convergence speed, interpretability, adaptive learning capacity, optimization performance, and real-time application. The method further involves a critical review of current restrictions like model complexity, training instability, hardware reliance, scarcity of benchmark datasets, and poor evaluation criteria for explainability in existing QIDRL systems. Finally, the reviewed findings were synthesized to identify research trends, technology advancements, open issues, and future directions for the development of scalable, transparent, and computationally efficient quantum-inspired intelligent analytics frameworks for next-generation data-driven applications.




Figure 1: System Architecture



3.1. Large Scale Data Source

The smallest layer of the proposed interpretable quantum-inspired DRL architecture for large-scale data analytics is the large-scale data source layer. This layer is in charge of collecting and coordinating the vast quantities of varied data produced by different real-world environments and intelligent systems. By combining structured databases, IoT and sensor networks, cloud and edge computing platforms, text documents, system logs, multimedia content (photos and videos), and social media data streams, the proposed architecture facilitates comprehensive analytical processing. The essential characteristics of big data, such as high volume, high velocity, high variety, high veracity, and high value, are present in these data sources, which significantly increase the complexity of data administration and intelligent decision-making processes. Additionally, the collected datasets could include high-dimensional, dynamic, noisy, and incomplete data that requires scalable and adaptive learning strategies for effective processing. By utilizing numerous large-scale data sources, the proposed system significantly boosts the capacity of quantum-inspired DRL models to carry out precise predictive analytics, anomaly detection, classification, optimization, and real-time decision support across a variety of application domains, including healthcare, cybersecurity, industrial automation, smart cities, renewable energy systems, and financial analytics.

3.2. Data Preprocessing and Feature Engineering

The proposed interpretable quantum-inspired DRL framework heavily relies on the data preprocessing and feature engineering stage, which enhances data quality, lowers noise, and converts unprocessed large-scale datasets into useful representations appropriate for intelligent analytics. Preprocessing methods are crucial for guaranteeing dependable model performance and precise decision-making because data gathered from diverse sources, including IoT devices, social media, healthcare systems, cloud platforms, and industrial sensors, frequently contains incomplete, inconsistent, and noisy information. To increase dataset consistency and analytical dependability, the data cleaning procedure first eliminates faulty entries, duplicate records, and unnecessary characteristics. Then, statistical approaches like mean replacement, interpolation, or predictive estimation are used to handle deficient data. The replacement for the missing value may be expressed as:

1 N

$$X_{missing} = -\sum_{i=1}^N X_i$$

Where N is the total number of valid observations utilized for estimation, X_i stands for available data samples, and $X_{missing}$ is the predicted missing value.

$$X_{norm} = \frac{X - X_{min}}{X - X_{min}}$$



$$\min \max$$

Where X_{norm} is the normalized output value between 0 and 1, X_{min} and X_{max} are the minimum and maximum feature values, respectively, and X is the initial feature value.

PCA Feature Extraction and Data Transformation

The proposed interpretable quantum-inspired deep reinforcement learning paradigm for large-scale data analytics relies heavily on Principal Component Analysis (PCA)-based feature extraction and data transformation. PCA is used to minimize dimensional complexity while maintaining the most important information needed for intelligent learning and decision-making, since large-scale datasets often include high-dimensional, redundant, and linked characteristics. By reducing the original high-dimensional dataset into a smaller collection of uncorrelated main components, PCA improves computing efficiency, lowers storage needs, speeds up model convergence, and reduces noise in the learning process in the suggested system. The quantum-inspired deep reinforcement learning model can now handle large-scale heterogeneous data more efficiently and correctly across a range of analytical applications thanks to this transition. The mathematical representation of the PCA transformation procedure is as follows:

$$Z = XW$$

Whenever Z is the converted lower-dimensional feature matrix generated after projection, W is the eigenvector matrix containing the main component directions, and X is the normalized input data matrix. The covariance matrix that PCA uses to find feature correlations is calculated as follows:

$$\sigma = \frac{1}{N-1} (X - \bar{X})^T (X - \bar{X})$$



Where N is the total number of observations, C is the covariance matrix, X is the input dataset, and $\bar{X}$ is the dataset's mean vector. The most relevant principal components are then chosen based on variance contribution using the eigenvalues and eigenvectors derived from the covariance matrix.

3.3. Interpretable Quantum-Inspired Deep Reinforcement Learning Framework

The fundamental intelligence element of the proposed large-scale data analytics architecture is the interpretable QIDRL framework. To accomplish scalable, adaptable, and transparent decision-making, this system combines explainable artificial intelligence (XAI) modules, deep neural learning mechanisms, RL methods, optimization approaches, and quantum-inspired computing concepts. The suggested methodology enhances convergence speed, optimization accuracy, interpretability, and computational scalability while processing high-dimensional heterogeneous datasets effectively. Quantum-Inspired Deep Neural Network (QIDNN), DRL Agent, Quantum-Inspired Optimization Layer, and interpretability XAI module are the four main submodules that make up the architecture. For intricate real-world applications, each module helps to improve intelligent analytics and trustworthy decision assistance.

3.4. Quantum-Inspired Deep Neural Network (QIDNN)

The Quantum-Inspired Deep Neural Network (QIDNN) is used to extract complex non-linear patterns and hidden feature representations from large-scale data using quantum-inspired computing notions such as superposition, probabilistic state representation, and quantum rotation operations. This module has improved adaptive intelligence, optimization efficiency, and feature learning capacities compared to classic neural networks. Another method to show the QIDNN activation process is:

n

$$h_i = f \left(\sum_{j=1}^n w_{i,j} x_j + b_i \right)$$

Where x_j is the input feature vector, $w_{i,j}$ is the connection weight between the neurons, b_i is the bias term, $f(\cdot)$ is the activation function, and h_i is the hidden layer output created by the quantum-inspired neural network.

3.5. Deep Reinforcement Learning Agent

The Deep Reinforcement Learning (DRL) agent may dynamically interact with the environment to get intelligent adaptive decision-making via states, actions, and rewards. The agent constantly learns optimum policies via trial-and-error. The objective is to maximize long-term rewards in complicated, large-scale analytical contexts. The reinforcement learning goal function is given by:

$$Q(s, a) = Q(s, a) + \alpha[r + \gamma \max_{a'} Q(s', a') - Q(s, a)]$$



Where $Q(s, a)$ signifies the action-value function, α is the learning rate, r is the reward value, γ is the discount factor, and $\max Q(s', a')$ is the future ideal reward prediction of the next state-action pair.

3.6. Quantum-Inspired Optimization Layer

The Quantum-Inspired Optimization Layer employs quantum-inspired optimization methods, such as quantum genetic algorithms, quantum particle swarm optimization, and probabilistic state updates, to boost model convergence speed, parameter optimization, and global search capacity. This module reduces computational cost and enhances learning stability in high-dimensional settings. The quantum-inspired optimization update equation is expressed as:

$$\theta_{t+1} = \theta_t + \beta \Delta \theta$$

The current parameter state is denoted by θ_t , the optimization update value is denoted by $\Delta \theta$, the optimization coefficient is denoted by β , and the optimized update parameter set to be used for the subsequent learning iteration is denoted by θ_{t+1} .

3.7. Interpretability Module (XAI)

The Interpretability Module (XAI) explains the prediction behavior, policy choices, and feature importance, which improves the transparency and dependability of the quantum-inspired deep reinforcement learning framework. This module incorporates explainability methods, including saliency maps, attention visualization, SHAP values, and decision-rule extraction, to provide interpretable analytical outcomes for important decision-making applications. The mathematical equation for the feature significance estimate is:

$$\frac{\delta_y}{\delta x_i}$$

Where i the relevance is score of the feature x_i , y is the model prediction output, and is the sensitivity of prediction to the input feature, which indicates the contribution of each feature to decision making.

3.8. Large Scale Data Analytics and Decisions Support

The Large Scale Data Analytics and Decision Support module is the last operational step of the proposed interpretable quantum-inspired deep reinforcement learning system, in which intelligent analytical outputs and optimized judgments are created from processed large-scale information. This module leverages the outputs derived from the quantum-inspired deep neural



network, reinforcement learning agent, optimization layer, and interpretability module to execute advanced analytical tasks, including classification, prediction, anomaly detection, resource optimization, pattern recognition, and real-time decision-making. The proposed system can efficiently analyze high-volume, high-velocity, and heterogeneous data generated from domains such as healthcare, cybersecurity, industrial automation, smart transportation, renewable energy systems, financial analytics, and IoT-based smart environments by exploiting scalable deep learning and quantum-inspired optimization capabilities. Moreover, the reinforcement learning system continually adapts to the changing environmental circumstances and dynamically improves the decision policies based on reward-driven learning techniques. The integrated interpretability module further promotes transparency by providing explanations on prediction behavior, feature significance, and policy choices, hence increasing trustworthiness and dependability for crucial applications. Therefore, the suggested framework is capable of providing accurate, scalable, adaptable, and explainable intelligent decision support for complicated large-scale data analytics environments while lowering computing complexity and boosting optimization efficiency.

3.9. Data Classifications

Data classification is a crucial analytical procedure inside the proposed interpretable quantum-inspired deep reinforcement learning system, whereby processed and modified data samples are organized into predefined categories based on identified patterns and feature representations. Classification techniques in large-scale data analytics are employed to discern significant information, identify anomalies, forecast outcomes, and facilitate informed decision-making across various fields, including healthcare diagnosis, cybersecurity threat detection, financial fraud analysis, smart transportation, and industrial automation. The proposed framework employs quantum-inspired deep neural networks and reinforcement learning techniques to enhance classification accuracy, adaptive learning ability, and computing efficiency for high-dimensional datasets. In the classification process, the features derived from preprocessing and PCA transformation are input into the quantum-inspired learning model, which learns optimum classification policies using reward-based optimization algorithms. The interpretability module elucidates categorization judgments by pinpointing significant factors that influence prediction results, hence enhancing transparency and reliability in cognitive analytics systems.



Table 1: Quantum-Inspired Data Classification

Input: Large-scale dataset D Output: Classified data labels C Step 1: Load dataset D Step 2: Perform data preprocessing - Remove noise - Handle missing values - Normalize data Step 3: Apply PCA feature extraction Step 4: Initialize QIDRL model parameters Step 5: Train a quantum-inspired deep neural network Step 6: Reinforcement learning agent selects actions Step 7: Compute reward and update model weights Step 8: Optimize parameters using quantum-inspired optimization Step 9: Predict class labels for input data Step 10: Generate interpretability explanations Step 11: Return classified output C End

Table 1 displays the proposed quantum-inspired data classification pseudocode, which begins with loading and preprocessing the large-scale dataset to remove noise, handle missing values, and normalize the input data for improving analytical consistency. Subsequently, PCA-based feature extraction is used to diminish dimensionality and provide significant feature representations for effective learning. The extracted features are subsequently supplied to the interpretable QIDRL framework, wherein the quantum-inspired deep neural network conducts intelligent feature learning, and the reinforcement learning agent adaptively modifies classification policies through reward-driven optimization. Moreover, the quantum-inspired optimization layer improves convergence rate and classification precision by effectively updating model parameters. The interpretability module produces clear explanations for categorization judgments by pinpointing significant contributing elements, thereby enhancing dependability and confidence in large-scale intelligent data analytics systems.

3.10. Performance Metrics

The performance evaluation of the proposed interpretable QIDRL framework examines its efficacy, scalability, optimization potential, and interpretability for extensive data analytics applications. The proposed system is assessed utilizing key evaluation measures such as classification accuracy, precision, recall, F1-score, convergence efficiency, computational complexity, reward optimization, and prediction reliability. These metrics assess the efficacy of the quantum-inspired learning framework in effectively managing high-dimensional heterogeneous datasets while ensuring transparency and adaptive decision-making performance. Moreover, the incorporation of quantum-inspired optimization and reinforcement learning techniques accelerates learning convergence, diminishes computing burden, and elevates predictive analytics efficacy relative to conventional deep learning methods. The classification accuracy of the proposed framework is determined as follows:



$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

Where TP indicates true positive samples, TN indicates true negative samples, FP indicates false positive predictions, and FN indicates false negative predictions. Elevated accuracy ratings indicate enhanced classification and analytical efficacy.

The precision measure assesses the accuracy of positive predictions and is expressed as:

$$Precision = \frac{TP}{TP + FP}$$

Where accuracy is defined as the percentage of accurately predicted positive occurrences relative to the total number of samples that were anticipated to be positive.

The following equation is used to determine the recall or sensitivity of the proposed system:

$$Recall = \frac{TP}{TP + FN}$$

Recall is a measurement that determines how well the framework is able to accurately identify true positive occurrences from the dataset.

Calculating the F1-score, which is a balance between accuracy and recall, involves the following:

$$F1 - Score = \frac{2 * precision * Recall}{precision + Recall}$$



Furthermore, this measure offers a balanced assessment of predicting performance, which is very useful in large-scale datasets that are uneven.

3.11. Predictive Analysis

The proposed interpretable quantum-inspired deep reinforcement learning architecture relies heavily on predictive analysis, which looks at large-scale historical and current data to predict future trends, outcomes, and decision-making patterns. To find hidden connections, improve prediction accuracy, and adapt to changing settings, the suggested system makes use of quantum-inspired deep neural networks and reinforcement learning approaches. By processing high-dimensional data from healthcare systems, cybersecurity networks, industrial automation, financial markets, and IoT platforms, the framework swiftly performs intelligent forecasting, anomaly prediction, risk assessment, and behaviour analysis. Furthermore, by clarifying the factors influencing prediction outcomes, the interpretability module increases transparency and improves confidence, dependability, and decision-making support in complex, large-scale analytical applications.

4. Results and Discussions

To enable high-dimensional data processing, intelligent learning, and optimization activities, the proposed interpretable QIDRL framework for large-scale data analytics needs scalable hardware resources as well as effective software environments. Programming platforms including Python, TensorFlow, PyTorch, Scikit-learn, NumPy, Pandas, and reinforcement learning libraries for creating quantum-inspired neural models, data preprocessing, feature extraction, predictive analytics, and interpretability mechanisms are among the software needs. Additionally, analytical interpretation and performance assessment may be done using visualization and explainability

tools like Matplotlib, SHAP, and LIME. From a hardware standpoint, the suggested framework can effectively handle large-scale heterogeneous datasets and intricate reinforcement learning operations thanks to high-performance computing systems with multi-core processors, GPU acceleration, large memory capacity, and cloud or edge computing support. According to the experimental analysis, in real-time intelligent analytics environments, the combination of quantum-inspired optimization and scalable computational resources greatly enhances convergence speed, predictive performance, computational efficiency, and adaptive decision-making capability while lowering processing delays.




Figure 2: Data Preprocessing



The efficacy of the data preparation step in the suggested framework is shown in Figure 2. The graphic illustrates how data cleaning eliminates outliers, duplicate records, and noisy samples while normalization improves the distribution of feature values. The processed dataset, therefore, becomes more balanced, organized, and appropriate for effective large-scale analytical learning.




Figure 3: PCA Feature Extraction

The dimensionality reduction potential of PCA-based feature extraction is seen in Figure 2. Important variance information is preserved as the original high-dimensional dataset is converted into lower-dimensional main components. In the quantum-inspired deep reinforcement learning paradigm, this transition lowers computing complexity while increasing learning efficiency.




Figure 4: QIDNN Performance

The training performance comparison between the proposed QIDNN model and a conventional deep neural network is shown in Figure 4. Because adaptive feature learning techniques and quantum-inspired optimization are integrated, the proposed QIDNN delivers greater training accuracy and quicker convergence.




Figure 5: Quantum-Inspired Optimization Performance



The optimization efficiency of the suggested quantum-inspired optimization layer in comparison to traditional optimization methods is shown in Figure 5. The suggested method improves learning stability and computing efficiency by achieving lower goal function values and quicker convergence.




Figure 6: Data Classification Results

The classification performance of the suggested framework utilizing evaluation metrics and a confusion matrix is shown in Figure 6. The usefulness of the suggested quantum-inspired learning framework in large-scale data classification tasks is shown by the results, which show high classification accuracy, balanced precision, recall, and F1-score.




Figure 7: Predictive Analysis Results

Figure 7 shows the performance of the predictive analysis in terms of the true values and the expected ones. The proposed interpretable reinforcement learning framework offers high forecasting reliability and strong predictive power. The anticipated outputs are in good agreement with the actual data patterns.

Figure 8 demonstrates the comparison of the proposed QIDRL framework with current deep learning models in terms of accuracy, F1-score, convergence speed, and execution time. The suggested framework surpasses the current techniques in terms of improved prediction performance and lower computing cost.




Figure 8: Overall Model Performance Comparison

5. Conclusions

The research provided a complete assessment of interpretable QIDRL methods for large-scale data analytics by combining quantum-inspired optimisation, deep neural networks, reinforcement learning, and explainable AI techniques into an integrated intelligent framework. The proposed system showed better classification accuracy, quicker convergence, improved predictive analysis, effective resource utilisation, and transparent decision-making for handling large-scale heterogeneous datasets. Moreover, the interpretability module enhanced the confidence and dependability of the model by explaining prediction behaviour and essential feature contributions. The total findings demonstrated that the proposed QIDRL framework enables scalable, adaptable, and computationally-efficient intelligent analytics for applications such as healthcare, cybersecurity, smart cities, finance, and industrial IoT systems. Future directions include hybrid quantum computing integration, enhanced explainable AI methodologies, and real-time edge-based intelligent analytics systems.

References

- 1) Pira, Lirandë, and Chris Ferrie. "On The Interpretability of Quantum Neural Networks." *Quantum Machine Intelligence* 6, no. 2 (August 28, 2024). <https://doi.org/10.1007/s42484-024-00191-y>.
- 2) Chen, Hao-Yuan, Yen-Jui Chang, Shih-Wei Liao, and Ching-Ray Chang. "Deep Q-learning With Hybrid Quantum Neural Network on Solving Maze Problems." *Quantum Machine Intelligence* 6, no. 1 (January 8, 2024). <https://doi.org/10.1007/s42484-023-00137-w>.
- 3) Cuéllar, Manuel P., M. C. Pegalajar, and C. Cano. "Automatic Evolutionary Design of Quantum Rule-based Systems and Applications to Quantum Reinforcement Learning." *Quantum Information Processing* 23, no. 5 (May 11, 2024). <https://doi.org/10.1007/s11128-024-04391-0>.
- 4) Barbosa, Diogo, Le Gruenwald, Laurent D'Orazio, and Jorge Bernardino. "QRLIT: Quantum Reinforcement Learning for Database Index Tuning." *Future Internet* 16, no. 12 (November 22, 2024): 439. <https://doi.org/10.3390/fi16120439>.
- 5) Dai, Xin, Tzu-Chieh Wei, Shinjae Yoo, and Samuel Yen-Chi Chen. "Quantum Machine Learning Architecture Search via Deep Reinforcement Learning." *QCE 2024*, September 15, 2024, 1525–34. <https://doi.org/10.1109/qce60285.2024.00179>.
- 6) Jha, Mayank Shekhar, Sameul Yen-Chi Chen, Chetan Kulkarni, and Joongheon Kim. "A



Comprehensive Review on Quantum Deep Neural Networks for Prognostics and Health Management: Fundamentals, Challenges and Opportunities.” *Engineering Applications of Artificial Intelligence* 177 (April 30, 2026): 114991.

<https://doi.org/10.1016/j.engappai.2026.114991>.

7) Gokhale, Shreya Sanjeev, Rishit Ravi Dhote, and Radhakrishnan Delhibabu. “A Review of Quantum Machine Learning Algorithms, Applications, and Emerging Advantages.” *Discover Computing* 29, no. 1 (April 24, 2026). <https://doi.org/10.1007/s10791-026-10085-1>.

8) Gayathri, T., G. Manjula, Harish H. Kenchannavar, Danthuluri Sudha, Santosh Kumar Jankatti, Ramandeep Kaur, and Bondu Venkateswarlu. “QuantumNeuroXAI: A Quantum-inspired Deep Learning Framework With Explainability for Brain Signal Analysis and Neurological Disorder Detection.” *Scientific Reports*, April 10, 2026. <https://doi.org/10.1038/s41598-026-47627-y>.

9) Ghisoni, Francesco, Matteo Borrotti, and Paolo Mariani. “A Large Scale Statistical Analysis of Quantum and Classical Neural Networks in the Medical Domain.” *Scientific Reports* 16, no. 1 (January 9, 2026): 3719. <https://doi.org/10.1038/s41598-025-33825-7>.

10) Liu, Dan, Yingzi Wu, Yiqun Kang, Linfei Yin, Xiaotong Ji, Xinghui Cao, and Chuangzhi Li. “Multi-agent Quantum-inspired Deep Reinforcement Learning for Real-time Distributed Generation Control of 100% Renewable Energy Systems.” *Engineering Applications of Artificial Intelligence* 119 (January 7, 2023): 105787. <https://doi.org/10.1016/j.engappai.2022.105787>.

11) Borella, Lorenzo, Alberto Coppi, Andrea Triossi, Jacopo Pazzini, Marco Zanetti, Andrea Stanco, and Marco Trenti. “Ultra-low Latency Quantum-inspired Machine Learning Predictors Implemented on FPGA.” *Machine Learning Science and Technology* 6, no. 4 (December 10, 2025): 045062. <https://doi.org/10.1088/2632-2153/ae25b5>.

12) Terven, Juan. “Deep Reinforcement Learning: A Chronological Overview and Methods.” *AI* 6, no. 3 (February 24, 2025): 46. <https://doi.org/10.3390/ai6030046>.

13) Alzubaidi, Laith, Jinglan Zhang, Amjad J. Humaidi, Ayad Al-Dujaili, Ye Duan, Omran Al-Shamma, J. Santamaría, Mohammed A. Fadhel, Muthana Al-Amidie, and Laith Farhan. “Review of Deep Learning: Concepts, CNN Architectures, Challenges, Applications, Future Directions.” *Journal of Big Data* 8, no. 1 (March 31, 2021): 53. <https://doi.org/10.1186/s40537-021-00444-8>.

14) Amini, Morteza, Mir Mohsen Pedram, AliReza Moradi, and Mahshad Ouchani. “Diagnosis of Alzheimer’s Disease Severity With fMRI Images Using Robust Multitask Feature Extraction Method and Convolutional Neural Network (CNN).” *Computational and Mathematical Methods in Medicine* 2021 (April 28, 2021): 1–15. <https://doi.org/10.1155/2021/5514839>.

15) Yan, Kehuan, Peichao Lai, Xianghan Zheng, Yang Yang, Yi Ren, Tuyatsetseg Badarch, and Yiwei Chen. “Quantum-inspired Neural Networks With Stochastic Dynamics for Multimodal Sentiment Analysis and Sarcasm Detection.” *Engineering Applications of Artificial Intelligence* 163 (October 24, 2025): 112923.

<https://doi.org/10.1016/j.engappai.2025.112923>.

16) Nguyen, Bac T., Van-Nui Nguyen, and Hiep L. Thi. “Quantum Neural Networks for Protein Post-translational Modification, Protein Function Prediction and DNA Analysis.” *International*



Journal of Modern Physics C, February 12, 2026.

<https://doi.org/10.1142/s0129183126430011>.

17) Sinha, Piyush Kumar, and Marimuthu R. “Conglomeration of Deep Neural Network and Quantum Learning for Object Detection: Status Quo Review.” *Knowledge-Based Systems* 288 (February 5, 2024): 111480. <https://doi.org/10.1016/j.knosys.2024.111480>.

18) Noé, Frank, Alexandre Tkatchenko, Klaus-Robert Müller, and Cecilia Clementi. “Machine Learning for Molecular Simulation.” *Annual Review of Physical Chemistry* 71, no. 1 (February 24, 2020): 361–90. <https://doi.org/10.1146/annurev-physchem-042018-052331>.